




SFFECO

Mobile CO2



SFFECO Mobile carbon dioxide fire extinguishers are known for its high reliable performance. The cylinders of CO2 fire extinguishers are seamless and are extruded from high grade Chrome Molybdenum Steel or Manganese or Carbon Steel.

Class of Fire



Solid matters forming glowing residues.
e.g. wood, rubber (car tires), paper, textiles.



Liquid combustible matter e.g. petrol,
oils, grease, ether, alcohol.

Technical Data

STANDARD MODELS

	TC10	TC25	TC30	TC60	TCB100
Extinguishing Agent	CO2	CO2	CO2	CO2	CO2
Total Weight (Kg)	38	96	102	195	145
Capacity (Kg)	10	25	30	60	45.5
Testing Pressure (Bar)	250	250	250	250	250
Coating	Electrostatic Polyester Powder				
Total Height (mm)	1060	1150	1150	1300	1150
Total Width (mm)	450	600	600	800	600
Total Depth (mm)	450	1250	1250	1600	1300
Hose Length (mm)	3500	3500	5500	5500	5500
Maximum Effective Range (m)	4	6	6	6	6
Duration of Discharge (Sec)	40-50	75-80	90-94	100-110	110-120
Storage Temperature (°C)	-20 to +60	-20 to +60	-20 to +60	-20 to +60	-20 to +60

In line with our policy of continuous product improvement, we reserve the right to modify specifications without prior notice.

Factory: 2nd Industrial Area - Al-Kharj Road - Riyadh

Tel. +966 1 2650070 - Fax. +966 1 2652190 - P.O. Box 4441 - E-mail : riyadh@sffeco.com.sa

SFFECO International - International Sales Office:

Jebel Ali - Free Zone - Dubai - U. A. E - Tel: +971 4 8861111 - Fax: +971 4 8862322

E-mail: dubai@sffecointl.ae

Jeddah :

Tel. 00966 2 6706009

Fax. 00966 2 6760307

E-mail: jeddah@sffeco.com.sa

Dammam :

Tel. 00966 3 8351961

Fax. 00966 3 8351968

E-mail: dammam@sffeco.com.sa

Madina :

Tel. 00966 4 8660959

Fax. 00966 4 8660969

Bahrain :

Telefax. 00973 17 721153

www.sffeco.com

