




SFFECO

Portable CO₂



SFFECO Portable Carbon Dioxide Fire Extinguishers are known for its high reliable performance and ease of handling. The cylinder for CO₂ Fire Extinguishers is seamless and extruded from high grade Chrome Molybdenum Steel or Manganese Steel or Carbon Steel.

Class of Fire



Solid matters forming glowing residues.
e.g. wood, rubber (car tires), paper, textiles.



Liquid combustible matter e.g. petrol,
oils, grease, ether, alcohol.

Technical Data

STANDARD MODELS

	CD 3-G	CD 5-G	CD 6-G	CD 5-L	CD 10-L	CD 15-L
Extinguishing Agent	CO ₂	CO ₂	CO ₂	CO ₂	CO ₂	CO ₂
Total Weight (Kg)	10.5	16.3	16.8	9	15	25
Capacity (Kg)	3	5	6	2.27	4.54	6.82
Testing Pressure (Bar)	250	250	250	250	250	250
Coating	Electrostatic Polyester Powder					
Total Height (mm)	565	700	790	670	700	950
Total Width (mm)	260	300	300	220	300	300
Cylinder Height (mm)	470	680	730	580	680	780
Cylinder Diameter (mm)	130	135	135	110	140	140
Hose Length (mm)	Only horn	1220	1220	Only horn	1220	1220
Maximum Effective Range (m)	5	5	5	5	5	5
Duration of Discharge (Sec)	9-11	9-11	9-11	7-9	9-11	10-12
Storage Temperature (°C)	-20 to +60	-20 to +60	-20 to +60	-20 to +60	-20 to +60	-20 to +60

In line with our policy of continuous product improvement, we reserve the right to modify specifications without prior notice.

Factory: 2nd Industrial Area - Al-Kharj Road - Riyadh

Tel. +966 1 2650070 - Fax. +966 1 2652190 - P.O. Box 4441 - E-mail : riyadh@sffeco.com.sa

SFFECO International - International Sales Office:

Jebel Ali - Free Zone - Dubai - U. A. E - Tel: +971 4 8861111 - Fax: +971 4 8862322

E-mail: dubai@sffecointl.ae

Jeddah :

Tel. 00966 2 6706009

Fax. 00966 2 6760307

E-mail: jeddah@sffeco.com.sa

Dammam :

Tel. 00966 3 8351961

Fax. 00966 3 8351968

E-mail: dammam@sffeco.com.sa

Madina :

Tel. 00966 4 8660959

Fax. 00966 4 8660969

Bahrain :

Telefax. 00973 17 721153

www.sffeco.com

